

TECHNO ADHESIVES COMPANY

12113 Mosteller Road
Cincinnati, Ohio 45241

Phone: (513) 771-1584
1-800-432-0107

Fax: (513) 771-1684
www.technoadhesives.com

TECHNO ADHESIVE NO. 122

CONTACT ADHESIVE

| | |
|-------------------|--|
| BASE: | Synthetic Elastomer |
| SOLVENT: | Acetate, Ketone Aliphatic Hydrocarbon Blend |
| COLOR: | Clear |
| CONSISTANCY: | Medium Thin Liquid, Brookfield 2/20 350 CPS @ 70°F |
| SOLIDS: | % by Weight 39% ± 2% |
| SPECIFIC GRAVITY: | 7.1 ± .2 Lbs./Gallon |
| DESCRIPTION: | This is a spray applied cement for bonding all types of foams to themselves and various substrates, such as cloth, wood, metal or other flexible foams. It has excellent application characteristics including quick tack, high coverage and high strength bonds. It produces soft non-dimpling bonds which will not harden or darken with age. Fabrics in contact with this bond line will not become stained after aging for long periods even when exposed to sunlight. This adhesive can be used to bond many other substrates in a contact form. Coat both substrates and allow to dry before contacting. |
| APPLICATION: | Spray Atomization Pressure 15 – 20 PSI Fluid Pressure 10 – 15 PSI |
| COVERAGE: | Square Foot/Gallon 400 - 600 |
| CAUTION: | This cement is flammable. Keep away from sparks and open flames |

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed, it being specifically understood that there are no warranties either expressed or implied incident to the sale of this product. No person is authorized or empowered to make any statement or recommendation concerning said product not contained herein, and any such statement or recommendation so made shall not bind the company. Users assume all risk and liability whatsoever resulting from the use of this product and must confirm the adaptability thereof by their own tests.