



MULTI GRIP-1000

PRE-CATALYZED TYPE II WOOD ADHESIVE

PHYSICAL PROPERTIES

Solids Content:	46.0 - 50.0%
Viscosity:	3000 - 6000 cps
Weight per Gal:	9.0 - 9.4 lbs.
pH Value:	2.0 - 3.0
Odor:	Slight, Characteristic
Shelf Life:	6 Months @ 75 DEG. F.
Clean Up:	Water
Base:	Pre- Cat Synthetic Resin
Chalk Point:	65 Deg. F.
Chalk Point of Winter Grade Adhesive:	60 Deg. F.

OUTSTANDING CHARACTERISTICS

1. Fast Set
2. Ease of use
3. High Solids
4. Uniform Results
5. Good Impact Resistance
6. Excellent Green Strength
7. Easy Clean Up
8. Pre-Catalyzed

Meets or exceeds the following Industry Standards:

- ANSI/HPMA 1983 Type II water resistance
- NWWDA Type I and Type II water resistance
- European Standard DIN EN 204 D3

Multi Grip 1000 is a shelf stable pre-catalyzed cross-linking wood adhesive. It can be applied by most conventional methods and can be used for hot press, cold press or radio frequency gluing. Multi Grip 1000 can also be used for a variety of wood assembly applications where a water resistant glue line is desired.

All ingredients approved under FDA 21 CFR 175.105 (indirect food contact)