

*Industrial Grade
Professional Quality*

*Industrial Grade
Professional Quality*




101
SOUND BUFFER
SOUND DAMPING
SPRAY

- High Density, Low Weight Compounds
- Greatly Reduces Road Noise & Panel Vibrations
- Clings to Wood, Plastic, Metal & Fiberglass
- Weatherproof, Can Be Used Inside or Outside of Vehicle

V&S 101 SOUND BUFFER.

DIRECTIONS FOR USE: Please read all instructions before proceeding.

1. Use only in well ventilated area. 2. All surfaces the are to be coated need to be cleaned thoroughly to insure the greatest adhesion. Metal surfaces should be cleaned with an appropriate metal cleaner so dust, dirt and grease are removed. Plastic surfaces also need to be cleaned, but roughing up or sanding is not required in most cases. Wood surfaces need to be free of all sawdust, dirt and oils. 3. All surfaces that are not to be coated should be covered or removed to protect from overspray. 4. Use only when ambient temperature is above 5 degrees Celsius or 40 degrees Fahrenheit. **5. Shake can vigorously for 1 full minute prior to use and periodically shake can during use.** 6. Apply in a slow sweeping motion being careful not to apply too thick a coat as runs may occur. 7. For best results, a second application is recommended but not required at temperatures equal to or greater than 24 degrees Celsius or 75 degrees Fahrenheit. Wait at least 2 hours before applying second application. At temperatures less than 24 degrees Celsius or 75 degrees Fahrenheit or in very high humidity areas, allow more time for drying. Product should be fully cured after 24 hours. 8. After each use, turn can upside down and spray for about 2 seconds. This will clear the nozzle for the next use. 9. Some minor, out gassing will occur but will disappear as the product becomes fully cured.

DANGER: Extremely flammable. Keep away from heat, sparks, or open flame. Vapors will accumulate readily and may ignite explosively. Keep area well ventilated during use and until vapors are gone. Harmful or fatal if swallowed. Do not take internally. Aspiration hazard. Use with adequate ventilation. Avoid inhalation of spray mist or vapors. To Contents under pressure. Do not puncture or incinerate can even when empty. Do not expose to temperatures exceeding 50°C / 122°F.

Manufactured for:
Adhesive Solutions, Inc.
Santa Fe Springs, CA 90670
www.adhesivesolutions.com
MADE IN THE USA
See S.D.S. for more additional information.

WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer or reproductive harm. For more information, go to www.P65Warnings.ca.gov.

CONTAINS: (CAS#) Hydrocarbon Propellant (68476-86-8),
Xylene (1330-20-7),
Rosin Ester (PROPRIETARY),
Styrene-Isoprene Block (025038-32-8),
Aromatic Hydrocarbon (108-88-3),
Silicon Dioxide (112926-00-8),
Inorganic Metal Oxide (7631-86-9),
Methyl Acetate (79-20-9),
Poly (Butadiene-Co-Styrene) (9003-55-8).

16oz can

KEEP OUT OF REACH OF CHILDREN

*Industrial Grade
Professional Quality*

*Industrial Grade
Professional Quality*